



## 62 SERIES


### STAINLESS STEEL BALL CONE CHECK VALVE



Prevents reverse flow with minimum change in flow velocity.

#### FEATURES

- Tight Shut Off
- No Radial Alignment Necessary
- Straight Through and Streamlined for Minimum Change in Velocity
- Ball-Cone™ Check is Spring-Loaded for Fast Seating Action (Constructed of RPTFE)
- All Wetted Metal Parts are 316 Stainless Steel
- Not Recommended for Reciprocating Pumps and Similar Applications Conducive to Repetitious Vibrations
- Optional Light Spring
- Soft Seat Design - Specify 62-500 Series



62-100 SHOWN

#### DIMENSIONS

PART NUMBER	PART NUMBER	SIZE	DIMENSIONS (IN.)			APPROX. OPEN PRESSURE	WT.
			A	B	C		
62-102-01	62-502-01	3/8"	2-1/8	11/8	11/8	1/2 PSIG	.38
62-103-01	62-503-01	1/2"	2-5/18	11/8	11/8	1/2 PSIG	.38
62-104-01	62-504-01	3/4"	2-7/8	13/8	11/2	1/2 PSIG	.75
62-105-01	62-505-01	1"	3-1/2	13/4	115/16	1/2 PSIG	1.45
62-106-01	-	1-1/4"	4-3/16	21/8	2 3/8	1/2 PSIG	2.75
62-107-01	-	1-1/2"	4-15/16	21/2	213/16	1/2 PSIG	3.94
62-108-01	-	2"	6	3	311/16	1/2 PSIG	6.30

## 61 SERIES


### BRONZE BALL CONE CHECK VALVE



Prevents reverse flow with minimum change in flow velocity.

#### FEATURES

- Tight Shut Off
- No Radial Alignment Necessary
- Straight Through and Streamlined for Minimum Change in Velocity
- Ball-Cone™ Check is Spring Loaded for Fast Seating Action (Constructed of RPTFE)
- Not Recommended for Reciprocating Pumps and Similar Applications Conducive to Repetitious Vibrations
- Optional Light Spring
- Soft Seat Design - Specify 61-500 Series
- Solder Connections - Specify 61-600 Series



61-100 SHOWN

#### DIMENSIONS

PART NUMBER	PART NUMBER	SIZE	DIMENSIONS (IN.)			APPROX. OPEN PRESSURE	WT.
			A	B	C		
61-101-01	61-501-01	1/4"	2-1/16	11/8	11/8	1/2 PSIG	.38
61-102-01	61-502-01	3/8"	2-1/8	11/8	11/8	1/2 PSIG	.38
61-103-01	61-503-01	1/2"	2-5/18	11/8	11/8	1/2 PSIG	.38
61-104-01	61-504-01	3/4"	2-7/8	13/8	11/2	1/2 PSIG	.75
61-105-01	61-505-01	1"	3-1/2	13/4	115/16	1/2 PSIG	1.45
61-106-01	61-506-01	1-1/4"	4-3/16	21/8	2 3/8	1/2 PSIG	2.75
61-107-01	61-507-01	1-1/2"	4-15/16	21/2	213/16	1/2 PSIG	3.94
61-108-01	61-508-01	2"	6	3	311/16	1/2 PSIG	6.30

